



Sales
London Tel: 44 (0) 208 854 0017

UK Sales Only – Screen Ink
Liverpool Tel: 0151 922 5665

www.apollocolours.co.uk

MERCURY GLOSS SCREEN INKS

MERCURY GLOSS screen inks have been developed to give excellent printability, screen stability, fast drying, good scuff resistance, and adhesion to a wide range of substrates. All types of paper and board may be printed, including cast coated such as Astralux. Many synthetic papers like Polyart, some top coated polyesters and metal foils can also be printed successfully. These inks are suitable for manual and automatic presses. They dry to a hard gloss finish dependant on the substrate, more absorbent materials giving a lower gloss. All colours are lead and heavy metal free, making them suitable for toys.

PRINTING & MILEAGE: All types of photostencil materials are suitable, and lacquer proof cut stencil films. 110T monofilament mesh is recommended for general work, but good results are obtained using 90 – 150T monofilament meshes. 60 – 75 sqm/lt may be expected when using a 110T mesh.

THINNERS:

Thinner	R265
Retarder	R107
Extra Retarder	R106

Recommended thinning:

Hand tables	10 – 20%
Semi-automatic presses	15 – 25%
Cylinder presses	25 – 35%

DRYING: When using the finer grades of screen mesh, prints will dry in 10 – 20 seconds at a temperature of 50 – 60 C. Prints will normally air dry in about 15 minutes dependent on ambient temperature, and air flow.

COLOURS: A full range, all colours lead free. Golds are supplied as a two pack system.

USES: Paper, board, corrugated board, wood, hardboard, glass, polyart, metal, metal foils and polyesters which have been top coated. Mercury Gloss inks are not recommended for outside exposure for prolonged periods.